

## AFI4

AFI4-###0.#0#4.1###

### Overview

- All-in-One conductivity sensor
- All wetted parts in PEEK
- Compact, food-safe, hygienic design
- 3-A sanitary standards and FDA-compliant, EHEDG-certified
- HART® communication protocol



### Technical data

#### Performance characteristics conductivity

Conductivity	14 selectable ranges
Min. measurable conductivity	50 $\mu\text{S/cm}$
Measuring ranges (selectable)	0... 500 $\mu\text{S/cm}$ 0... 1 mS/cm 0... 2 mS/cm 0... 3 mS/cm 0... 5 mS/cm 0... 10 mS/cm 0... 20 mS/cm 0... 30 mS/cm 0... 50 mS/cm 0... 100 mS/cm 0... 200 mS/cm 0... 300 mS/cm 0... 500 mS/cm 0... 1000 mS/cm
Max. measuring span	1000 mS/cm
Min. measuring span	500 $\mu\text{S/cm}$
Max. measuring error	$\pm 1.0\%$ FSR, 0 ... 1 mS/cm to 0 ... 500 mS/cm $\pm 1.5\%$ FSR, 0 ... 1000 mS/cm $\pm 1.5\%$ FSR, 0 ... 500 $\mu\text{S/cm}$
Reference conditions for max. measuring error	Sensor incl. transmitter @ 25°C ambient temperature
Reference temperature	25 °C, adjustable
Repeatability	< 0.5 % FSR, > 1 mS/cm
Compensated temperature range	-20 ... 150 °C
Temperature compensation	0.0 ... 5.0 % FSR/K, adjustable
Step response time, T90	$\leq 2.0$ s
Sample time	$\leq 0.3$ s

#### Performance characteristics conductivity

Temperature coefficient (Factor of change in process temperature from 25°C)	$\leq 0.1\%$ FSR/K
Temperature coefficient (Factor of change in process temperature from 25°C) (0 ... 500 $\mu\text{S/cm}$ )	$\leq 0.3\%$ FSR/K
<b>Performance characteristics concentration</b>	
Concentration	4 factory set media
HNO <sub>3</sub> (nitric acid)	0... 25 % by weight, 0 ... 80 °C 36 ... 82 % by weight, 0 ... 80 °C
NaOH (caustic soda)	0... 15 % by weight, 0 ... 90 °C 25 ... 50 % by weight, 0 ... 90 °C
Customer defined media	Customer defined (30 point lookup table)

#### Performance characteristics temperature

Temperature	Free programmable range
Measuring range	-20 ... 150 °C
Step response time, T90	$\leq 15$ s
Max. measuring error	$\pm 0.4$ K
Reference conditions for max. measuring error	Sensor incl. transmitter @ 25°C ambient temperature
Temperature coefficient (Factor of change in process temperature from 25°C)	$\leq 0.5\%$ FSR/K

#### Process conditions

Process temperature	-20 ... 140 °C, permanent 140 ... 150 °C, max. t < 1 h
Process pressure	$\leq 25$ bar
SIP/CIP compatibility	< 60 min, @ medium temperature up to 150 °C

#### Process connection

Connection variants	G 1 A hygienic
---------------------	----------------

# AFI4

AFI4-###0.#0#4.1###

## Technical data

### Process connection

Immersion length	Refer to section "Dimensional drawings"
Wetted parts material	PEEK Natura
Surface roughness wetted parts	Ra ≤ 0.8 µm

### Ambient conditions

Operating temperature range	-30 ... 80 °C , with DFON touch screen -40 ... 85 °C , without DFON touch screen
Degree of protection (EN 60529)	IP 67 IP 69K , with appropriate cable
Humidity	< 98 % RH , condensing
Insulation voltage	500 V AC
Vibration (sinusoidal) (EN 60068-2-6)	1.0 mm p-p (2 ... 13.2 Hz), 0.7 g (13.2 ... 100 Hz), 1 octave / min.

### Output signal

Conductivity/Concentration	4 ... 20 mA 4 ... 20 mA , + HART®
Temperature	4 ... 20 mA
Relays	2 relays included in the display
Current rating	100 mA , max.
Interface	IO-Link 1.1 With HART® modem With FlexProgrammer 9701

### HART® interface

Properties	Universal commands Common-practice commands Conductivity device family commands Device Specific Commands For more information please see 'HART Field Device Specification'
Protocol	HCF standard, Rev.7

### IO-Link interface

Version	1.1
Device profile	Smart Sensor Profile
IODD	Baumer-AFIx-20190110-IODD1.1.xml
Port type	Class A
Transmission rate	38,4 kbaud (COM2)
Min. cycle time	8,4 ms
Process data length	128 bit
SIO-mode	Yes
Process data (cyclic)	Switch state Signal analog output 1 Signal analog output 2 Temperature Unit temperature Conductivity Concentration Actual measuring range
Adjustable data (acyclic)	Measuring mode Sensor calibration Media calibration Reference temperature Temperature compensation Switch parameters

### IO-Link interface

Dual channel	Conductivity/Concentration
Dual channel 2	Temperature
Dual channel 3	Relay 1
Dual channel 4	Relay 2

### Housing

Style	FlexHousing, Ø80 mm Bottom process connection Rear process connection
Overall size	Refer to section "Dimensional drawings"
Material	AISI 304 (1.4301)

### Electrical connection

Connector (available for left side)	M12-A, 5-pin, stainless steel M16x1.5, plastic M16x1.5, stainless steel M20x1.5, plastic M20x1.5, stainless steel
Connector (available for right side)	M16x1.5, plastic M16x1.5, stainless steel M20x1.5, plastic M20x1.5, stainless steel M12-A, 4-pin, stainless steel, 4 ... 20 mA output M12-A, 8-pin, stainless steel, 4 ... 20 mA + relay output

### Power supply

Voltage supply range	15 ... 35 V DC 18 ... 30 V DC , with IO-Link
Current consumption (no load)	150 mA , max.
Power-up time	≤ 10 s , without DFON touch screen ≤ 16 s , with DFON touch screen

### Factory settings

HART®	Activated
IO-Link	Disabled
Output mode	Conductivity
Conductivity Range 1	0... 200 mS/cm
Conductivity Range 2	0... 20 mS/cm
Conductivity Range 3	0... 2 mS/cm
Conductivity Range 4	0... 500 µS/cm
Temperature output	0... 150 °C
Output damping	0.00 s
Temperature compensation Range 1-4	2.00 % FSR/K
Output lower current limit	3.70 mA
Output upper current limit	21.00 mA

### Compliance and approvals


EMC	EN 61326-1:2013
Hygiene	3-A (74-07) EHEDG EL Class I FDA (21 CFR 177.2415)

# AFI4

AFI4-###0.#0#4.1###

## Operating conditions

Measuring range	Max. measuring error	Conductivity	Media group	Media
0 ... 500 µS/cm	1,5 % FSR	7,5 µS/cm		Ultra-pure water
0 ... 1 mS/cm	1,0 % FSR	10 µS/cm	Water	Pure water
0 ... 2 mS/cm	1,0 % FSR	20 µS/cm		Process water
0 ... 3 mS/cm	1,0 % FSR	30 µS/cm		Drinking water
0 ... 5 mS/cm	1,0 % FSR	50 µS/cm		Beer
0 ... 10 mS/cm	1,0 % FSR	100 µS/cm	Food & Beverage	Milk
0 ... 20 mS/cm	1,0 % FSR	200 µS/cm		Orange juice
0 ... 30 mS/cm	1,0 % FSR	300 µS/cm		Apple juice
0 ... 50 mS/cm	1,0 % FSR	500 µS/cm		Phosphoric acid
0 ... 100 mS/cm	1,0 % FSR	1 mS/cm	Process	Hydrochloric acid
0 ... 200 mS/cm	1,0 % FSR	2 mS/cm		Sodium hydroxide
0 ... 300 mS/cm	1,0 % FSR	3 mS/cm		
0 ... 500 mS/cm	1,0 % FSR	5 mS/cm		
0 ... 1000 mS/cm	1,5 % FSR	15 mS/cm		



## Display

### General information

Panel type	FSTN Graphical LCD
Display range	-9999 ... 99999
Max. digit height	22 mm
Material	Polycarbonate

### Ambient conditions

Operating temperature range	-30 ... 80 °C
Optimal readability temperature range	-10 ... 70 °C
Degree of protection (EN 60529)	IP 67 IP 69 K

### Input signal

Input signal from transmitter	Digital, 2-way for communication between transmitter and display
Update time	≤ 1 s, max. 0,3 s, typ.

### User configurable data

Error- / Warning-indication	Individually configurable display and backlight indication in white, green or red colour, steady or flashing light. Configurable limits over the range
Media description	Customer programmable e.g. "MILK", "Water", "NaOH"
Measuring unit	µS/cm mS/cm % °C °F
User defined measuring unit	8 × 20 pixel matrix


### Relays

Contacts	2 x solid state relays
Max. load current	75 mA
Max. switching voltage	60 V


## Selectable display views




Conductivity value with medium and additional values



Medium with additional values



Bar chart with additional values and medium



Concentration with additional values and medium

# AFI4


AFI4-###0.#0#4.1###

## Display


### Selectable display views



Conductivity value with measuring point (TAG)



Medium with measuring point (TAG)



Bar chart including temperature



Conductivity and concentration value



White background



Green background



Red background




Exemplary error message

## Dimensional drawings


### Housing



FlexHousing, available with or without DFON touchscreen



FlexHousing with bottom process connection




FlexHousing with rear process connection

# AFI4


AFI4-###0.#0#4.1###

## Dimensional drawings


### Process connection




G 1 A hygienic (BCID: A04), PEEK, 37 mm



G 1 A hygienic (BCID: A04), PEEK, 60 mm



G 1 A hygienic (BCID: A04), PEEK, 83 mm




Sensor tip with integrated Pt100 sensor element

# AFI4

AFI4-###0.#0#4.1###

## Electrical connection


### M12-A, 5-pin




Left side connection

Right side connection

### M12-A, 4-pin



### M12-A, 8-pin



### Left side connection (front view): M12-A, 5-pin

Function	Pin assignment
+Vs Power supply + 15 ... 35 V DC	1
GND (0 V) Power supply - 15 ... 35 V DC	3
lout1+ Conductivity + 4 ... 20 mA	4
lout- Conductivity - 4 ... 20 mA	2
IO-Link IO-Link / SW	5

lout- is internally connected as common for both Conductivity/Concentration and Temperature output.

### Left side connection (front view): Cable gland

Function	Recommended wiring
+Vs Power supply + 15 ... 35 V DC	BN
GND (0 V) Power supply - 15 ... 35 V DC	BU
lout1+ Conductivity + 4 ... 20 mA	BK
lout- Conductivity - 4 ... 20 mA	WH
IO-Link IO-Link / SW	GY

lout- is internally connected as common for both Conductivity/Concentration and Temperature output.

### Right side connection (front view): M12-A, 4-pin

Function	Pin assignment
lout2+ Temperature + 4 ... 20 mA	4
lout- Temperature - 4 ... 20 mA	2
S1 External input n.c. / 24 V DC	1
S2 External input n.c. / 24 V DC	3

lout- is internally connected as common for both Conductivity/Concentration and Temperature output.

### Right side connection (front view): M12-A, 8-pin

Function	Pin assignment
lout2+ Temperature + 4 ... 20 mA	2
lout- Temperature - 4 ... 20 mA	7
S1 External input n.c. / 24 V DC	1
S2 External input n.c. / 24 V DC	8
R11 Relay 1	5
R12 Relay 1	6
R21 Relay 2	3
R22 Relay 2	4

lout- is internally connected as common for both Conductivity/Concentration and Temperature output.

### Right side connection (front view): Cable gland

Function	Recommended wiring
lout2+ Temperature + 4 ... 20 mA	BN
lout- Temperature - 4 ... 20 mA	BU
S1 External input n.c. / 24 V DC	WH
S2 External input n.c. / 24 V DC	RD
R11 Relay 1	GY
R12 Relay 1	PK
R21 Relay 2	GN
R22 Relay 2	YE


lout- is internally connected as common for both Conductivity/Concentration and Temperature output.

# AFI4

AFI4-###0.#0#4.1###

## Electrical connection

### Terminal assignment transmitter




### Terminal assignment DFON display



The ground connection is to be connected with the cable shield if using cable gland and shielded cable.

### Replacement switching diagram



# AFI4

AFI4-###0.#0#4.1###

## Ordering information

Ordering key - Configuration possibilities see website

	AFI	4	-	#	#	#	0	.	#	0	#	4	.	1	#	#	#
<b>Product</b>	AFI																
<b>Type</b>																	
Compact version		4															
<b>Housing</b>																	
Bottom process connection																	5
Rear process connection																	6
<b>Electrical connection</b>																	
2 x M16x1.5 cable gland																	8
1 x M16x1.5 + 1 x M20x1.5 cable gland																	A
2 x M20x1.5 cable gland																	B
1 x M12-A, 5-pin + 1 x M12-A, 4-pin																	C
1 x M12-A, 5-pin + 1 x M12-A, 8-pin																	D
<b>Material of el. connection</b>																	
Plastic																	1
Stainless steel, AISI 304 (1.4301)																	3
<b>Cable length (cm)</b>																	
No cable, compact version																	0
<b>Display</b>																	
Without display																	1
With display, with activated relays																	4
<b>Safety</b>																	
Standard																	0
<b>Configuration</b>																	
No configuration																	0
Configuration of range																	1
Configuration of range + display incl. 2 relays																	3
<b>Output</b>																	
2 x 4...20 mA, HART																	4
<b>Version</b>																	
IO-Link																	1
<b>Process connection</b>																	
G 1 A hygienic, PEEK, length: 37 mm. (A04)																	1
G 1 A hygienic, PEEK, length: 83 mm. (A04)																	2
G 1 A hygienic, PEEK, length: 60 mm. (A04)																	3
<b>Approvals</b>																	
Standard approvals																	0
3-A / EHEDG																	1
3-A																	2
<b>Calibration certificate</b>																	
No																	0
Calibration certificate, conductivity (5 points)																	1
Calibration certificate, temperature. (3 points)																	2
Calibration certificate, conductivity (5 points) and temperature (3 points)																	3

2020-03-04 The product features and technical data specified do not express or imply any warranty. Technical modifications subject to change.